LEDCOMS VISUAL CO., LIMITED

Tel: +86-755-23197520 Email: info@ledcoms.com
Building C, Huafa Industrial Park, Gongming Town, Guangming District, Shenzhen, 518106, China
website: www.interactiveledfloor.com

RENTAL LED FLOOR DISPLAY SPECIFICATIONS

Module						
Pixel Pitch	2.976mm	3.91mm	4.81mm	5.2mm	6.25mm	7.8mm
Pixel Configuration	3-IN-1 SMD1415					
Pixel Density(dot/sqm)	112,896	66,536	43,264	36,864	25,600	16,384
Size(WxH)	250mm x 250mm					
Resolution(WxH)	84 x 84	64x64	52x52	48x48	40x40	32x32
Panel						
Size(WxH)	500mm x 500mm					
Resolution	168 x 168	128x128	104x104	96x96	80x80	64x64
Weight	12.5 kg/panel					
Module Quantity	4pcs(2x2)					
Material	Aluminum					
Display						
Interactive Function	Yes(optional)					
IP Rating	IP54(IP65 optional)					
Brightness	>1500 nits (256 levels adjustable)					
Weight Capacity	>2000kg/sqm					
Viewing Angle	Horizontal 120°; Vertical 120°					
Gray Scale	16 bit					
Refresh Rate	>1920Hz					
Color Temperature	3200-9300K adjustable					
Input Power Source	AC100-240V; 50/60Hz					
Average Power Consumption	240W/sqm					
Maximum Power Consumption	650W/sqm					
Operation Temperature	-20°C to +50°C					
Relative Humidity	10%-90%RH					
Life Span	100,000 hours					
Serviceability	Rear access					
Control Distance	CAT5 cable: <100m; Single mode fiber: <10km					